



F234

## F234

### Material used

Palm – Natural grain leather of 20 cm length and that of 1.0-1.1 mm thick  
 Back – Natural split leather  
 Cuff – Natural split cuff  
 Binding – NA  
 Liner – NA

### Available Size

7, 8, 9, 10, 11

### Color

Natural

### Features:

Natural grain welder glove with 15 cm split cuff  
 Provides good mechanical resistant and comfort  
 Total wt/ pair (g)- 250 gm  
 Gross wt/ carton- 13.2 kg  
 Chromium VI free leather according to EN 420:2003 + A1:2009

### Specifications:

Palm: 20 cm length and 1.0-1.1 mm thick  
 Stitching: 100% Kevlar®  
 Cuff: 15 cm natural split cuff  
 Weight (DZP): 3000 (±10) gm



## WELDER GLOVES

*Natural grain leather welder glove with 15 cm split cuff*



### MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City  
 Kolkata 700091, India

T: +E : [safety@mallcom.in](mailto:safety@mallcom.in), w : [www.mallcom.in](http://www.mallcom.in)



## Safe hands!!

### Instruction for use

The glove should not be worn when it exists a risk of entanglement by moving parts of machines.

Gloves do not provide any protection against electric shock when intended to arc welding.

Type A gloves are recommended for other welding processes.

There is no standardized test method at present for detecting U.V. penetration of materials for gloves.

With arc welding installations, it is not possible to protect all parts conducting the welding voltage against direct contact for operational reasons.

Can be used for working near furnaces (but the glove do not affect any protection against large splashes of molten metal), Metallurgical product handling (the glove allow the handling of hot pieces not above 100°C).

### Instructions for storage:

Store the gloves in cool dry place and out of reach of sunlight in their original carton and packing.

Using life depends on character of activity and usage frequency.

*Mallcom welder gloves provides superior comfort and dexterity with unparalleled mechanical resistant properties*

### Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines.

### Instructions for cleaning / maintenance:

It cannot be cleaned

Do not clean in washing machine.

Put the gloves on clean and dry hands.

Check inside and out of gloves before re-use them.

### Packaging Instruction:

36 pairs in a carton

EN 388



2132

Performance according to EN 388:2003 :

- 2. Resistance to abrasion (from 0 to 4)
- 1. Resistance to cut (from 0 to 5)
- 3. Resistance to tear (from 0 to 4)
- 2. Resistance to puncture (from 0 to 4)

EN 407



X1XXXX

EN 407 :X1XXXX

X. Resistance to flammability (from 1 to 4)

1. Resistance to contact heat (from 1 to 4)

X. Resistance to convective heat (from 1 to 4)

X. Resistance to radiant heat (from 1 to 4)

X. Resistance to small projection from molten metal (from 1 to 4)

X. Resistance to large projection from molten metal (from 1 to 4)

### Applications:

Welding operation

Hot metal handling

Hot metal sheet processing

MIG & TIG applications

