



P35NBG

#### Features:

Seamless knitting construction  
Open back configuration for better ventilation.

Ergonomically correct design conforms snugly to the natural shape of the hand, increasing comfort and reducing hand fatigue.

Colour coded overlock binding helps to identify different sizes (07- Red, 08- Yellow, 09- Brown, 10- Black).

Nitrile dipped palm provides excellent puncture and abrasion resistance properties, also provide assistance to handling chemicals and oils.

## P35NBG

#### Material used

Palm:- 1.1 mm thick sandy finished palm

Coating: - NBR compound coated

Liner:- Polyester

Binding: - Polypropylene yarn

#### Sizes

7, 8, 9, 10, 11

#### Color

Liner Color: Grey

Coating Color: Black

#### Specifications

Gauge: 15

Weight: 500-700 g/dzp

Finishing: Sandy Finish



## NITRILE GLOVES

*Grey Polyester 15 gauge seamless liner coated with black coloured Nitrile compound, Sandy finish.*



#### MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City

Kolkata 700091, India

T: +E : [safety@mallcom.in](mailto:safety@mallcom.in), w : [www.mallcom.in](http://www.mallcom.in)



## Safe hands!!

### Limits to use

Do not use this glove out of its usage specifications defined in the instructions above. This glove does not contain substance known as being carcinogenic, neither toxic, nor likely to cause allergies to the sensitive people.

### Instructions for storage:

Store in a cool, dry place; away from frost and light in their original packaging.

*Polyester seamless with  
Nitrile coating ensures  
protection against chemical  
as well as mechanical threats*

### Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines

### Instructions for cleaning:

No specific cleaning or maintenance for this type of glove.

### Packaging Instruction:

1 dozen pairs in a polybag  
10 poly bags in a carton  
120 pairs in a carton  
(240 pairs/carton option also available)



Performance according to EN 388:2003 :

- 4. Resistance to abrasion (from 0 to 4)
- 1. Resistance to cut (from 0 to 5)
- 2. Resistance to tear (from 0 to 4)
- 1. Resistance to puncture (from 0 to 4)



### Applications:

Construction Works.  
Lumber and mill works  
Metal/aluminium sheet handling  
Machine parts assembling disassembling  
Gardening  
Agricultural applications  
Motor industry



### MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City  
Kolkata 700091, India

T: +E : [safety@mallcom.in](mailto:safety@mallcom.in), w : [www.mallcom.in](http://www.mallcom.in)