

**PRODUCT : RETRACTABLE FALL ARREST BLOCK**  
**REF. NO. : PCGS 10 To 15**

DOC. NO.	03.05
ISSUE	01
REVISION	01
DATE	30-05-2011

CONFORMING TO EN 360:2002



1	PHYSICAL PARAMETERS	General		<ul style="list-style-type: none"> <li>Robust and Durable Plastic casing made from high impact strength polymer.</li> <li>Has a Swivel Anchorage eye at one end; and a Swivel Steel Snap Hook PN 123 at the retractable end.</li> </ul>
2	DIMENSIONS OF THE CASING			Width 172 mm    Height 460 mm    Thickness 87 mm
3	MECHANICAL CHARACTERISTICS		Breaking Strength Breaking Force Breaking Distance Minimum Clearance Weight Temp. Range	15 kN  Less than 6 kN  0.5 Mtr.  1.5 Mtr. Below User's feet  6.0 To 6.9 Kg. -30 <sup>0</sup> C to +50 <sup>0</sup> C
4	HARNESS END CONNECTOR PN 123 (Swivel Snap Hook with Load Indicator)		Weight  Breaking Load Opening Material	345 gm.  23 kN 11.5 mm Alloy Steel
5	TOP END CONNECTOR PN 112		Weight Breaking Load Opening Material	160 gm. 23 kN 17 mm Alloy Steel
6	RETRACTABLE LANYARD		Material diameter	Galvanized Steel 4.8 mm

		Breaking Strength	Greater than 15 kN
		Maximum Length	10 To 15 meters

### VITAL TEST COMPLIANCE

EN 360:2002 TEST	APPARATUS IN USE	TESTING COMPLIANCE
Clause 4.3 (Locking after conditioning)	A Conditioning Apparatus; a rigid mass of 35 Kgs	When tested according to this clause, the Fall Arrestor locks before the mass touches the ground and remains locked until released.
Clause 4.4 (Static Strength)	Force measuring Tensile Testing Machine.	When subjected to a static force of 12 kN for 3 Min., the assembly of the block and the lanyard shows no sign of any damage or fracture.
Clause 4.5 (Dynamic Performance)	A rigid anchorage structure; Force measuring apparatus, with Peak-Force recorder; Rigid steel mass of 100 kgs, of nominal diameter 200 mm, and an eyebolt attached; A Quick Release device.	When subjected to a fall with a rigid mass of 100 Kg., the breaking force is less than 6 kN, and the arrest distance is less than 2 m.
Clause 4.7 (Corrosion Resistance)	A Corrosion Test Apparatus	When subjected to a neutral salt spray for 24 hours, There is no evidence of corrosion on any of the exposed, as well as the internal metal parts, which can affect the function of the device.