

**PRODUCT: KERNMANTLE ROPE ANCHORAGE LINE
(To be used with KARAM Fall Arrester)**



DOC. NO.	QF/RD/05
ISSUE	01
REVISION	01
DATE	20-08-2014

1	PHYSICAL PARAMETERS	GENERAL	<ul style="list-style-type: none"> Made of Polyamide Kernmantle rope of \varnothing 11 mm One side loop and other end stop Knot Also available with both side loops. Kernmantle Rope anchorage line is designed to stretch under a heavy load to absorb the shock of a fallen climber. Useful for applications such as rappelling, hauling and tower work. Rope capable of withstanding multiple falls. Available in length of 10m, 20m, 30m, 40m, 50m. (Longer lengths are also available on request) Ref. no. of 10m anchorage line: PN 910 (KRKD11) Ref. no. of 20m anchorage line: PN 920 (KRKD11) Ref. no. of 30m anchorage line: PN 930 (KRKD11) Ref. no. of 40m anchorage line: PN 940 (KRKD11) Ref. no. of 50m anchorage line: PN 950 (KRKD11)
		WEIGHT	10 meter: - 750 gm \pm 10 gm 20 meter:- 1550 gm \pm 10 gm 30 meter:- 2320 gm \pm 10 gm 40 meter: - 3060 gm \pm 10 gm 50 meter:- 3620 gm \pm 10 gm
		MATERIAL	Polyamide
		BREAKING STRENGTH	23 kN (Min.)
2	VITAL TEST COMPLIANCE	STATIC STRENGTH	CONFORMITY 15 kN sustained for 3 minutes without any failure
		DYNAMIC PERFORMANCE	CONFORMITY Maximum breaking force does not exceed 6 kN in the line when tested with a test Mass of 100 kg after raising the mass as far above the arrester as the lanyard and connector permits

