

**PRODUCT : WORK POSITIONING LANYARD
WITH GRIP ADJUSTER**

REF. NO. : PN 242

DOC. NO.	QF/RD/05
ISSUE	01
REVISION	01
DATE	26-11-2013



CONFORMING TO EN 358: 1999

1	PHYSICAL PARAMETERS	GENERAL		<ul style="list-style-type: none"> Rope ends spliced and covered with polyethylene protective sleeve. Abrasion resistant thimbles provided within loops. Karabiner (PN 112) provided at one end and one karabiner (PN 112) equipped with Rope Grab RG 03 for attachment. Easy adjustment by using Rope Grab RG 03 Ø14 mm three strand Polyamide Twisted rope. Green Tracer in the rope to indicate degradation of material. Adjustable length up to max. 2 mtr. Rope breaking strength min. 25 kN
			WEIGHT	1125 gm ± 10 gm
2	METALLIC ASSEMBLY	ROPE GRAB RG 03	MATERIAL PLATING FINISH	High strength steel Zinc plated Deburred and polished
		KARABINER PN 112	MATERIAL BREAKING STRENGTH FINISH	Alloy steel 25 kN (Min.) Silver/Golden Yellow Galvanized
3	VITAL TEST COMPLIANCE	STATIC STRENGTH	CONFORMITY	Sustains a force of 15 Kn per 3 minutes without separating, tearing or rupture of the lanyard or any element connected to it.
		DYNAMIC PERFORMANCE	CONFORMITY	Sustains a Free fall from 1 meter height with a test mass of 100 kg without separating, tearing or rupture of any lanyard element.