



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS
Chemical	Chemical handling
Pharmaceuical	Labs
Oil & gas	Paint shop
Iron & steel	Grinding
Automoive	Medical applicaion

SPECIAL FEATURES













STANDARD : ANSI Z87.1

ET-49A – Safety Goggles

COMPONENT	MATERIAL	ADVANTAGE	
Lens	Polycarbonate	Single & cylinder lens	
Frame	PVC / vinyl	Flexible fi ng goggle with venilaion system	
Nose piece	PVC	Universal integral to frame	
Head band	Texile elasic	Adjustable elasic	

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	LIQUID SPLASH RESISTANCE	COATING	WEIGHT
Polycarbonate	1	2-1.2	B (120m/s)	3	K&N	75 g.

FEATURES

Polycarbonate lens with sot PVC or vinyl frame

Fully adjustable Headband atached to fits most users

Sot frame conforms to facial contours for a very comfortable fit, long ime use

Ani-fog & hard coaing on lens

Lens filters out 99.9% of harmful UV light

Lens provides high velocity impact & splash protecion around the eyes

Universal fit sot nose bridge conforms to facial contours to ensure a comfortable fit

Vening system that circulates air, yet prevent dust

Incredibly light, resilient, durable & over the glass protecive eyewear for all day wear

Suitable for different work environment & for both men and women

APPLICATION

Protects eyes exposed to high level impacts

Best used for protecion agains flying small fragments, liquid splashes, fumes, sparks etc.

Also protects against irritaing mist and potenially infecious materials (Lab environment)

STORAGE

Can be stored in the dark for up to 2 years

Do not store in direct / high heat or sunlight as this may distort the colour

Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING	PACKING
Clean it with the sot cloth	50 pieces per cartoon