



**FUSION 6000 Series
- Safety Helmet**

STANDARD : EN 397, CE

INDUSTRY	IDEAL APPLICATIONS
Cement	Construction & projects works
Automotive	Material handling
Power & utilities	Shop floor
Metals & mining	Packaging
Iron & steel	Maintenance

SPECIAL FEATURES

LIGHT WEIGHT	RECYCLABLE	STRONG & DURABLE	TEMPERATURE RESISTANT	RATCHET FIT
--------------	------------	------------------	-----------------------	-------------

COLOURS: White Blue Yellow Red Green Orange

COMPONENT	MATERIAL	ADVANTAGES
Shell	ABS (Acrylonitrile Butadiene Styrene)	Resistant to high radiant heat
Peak	ABS	20 mm, peak protects eye & face from falling objects
Brim	ABS	Rim around the shell, drains rain water
Cradle	LDPE / Textile	8-point adjustment, perfect load distribution
Head band	LDPE	Universal fit, dia. 52 cm – 66 cm
Sweat band	Brushed cloth on foam	Sweat absorbent, long time use
Chin strap	PP	Holds the shell, universal fit
Chin strap clip	Nylon	Attachment between shell and chin strap
Ratchet	Nylon	Fully adjustable, smooth & universal fit
Slot	Universal slots on the both side	Compatible with head & face PPE accessories
Ventilation	Both side of the crown ventilated	3 point ventilation on each side for air circulation

FEATURES

Shell made of ABS compound
8-point plastic / textile suspension with slip fit or ratchet fit adjustment
Unique crown ventilation system provides air circulation & comfort
High quality sweat band provides comfort
Tensile strength is higher than HDPE helmets yet light weight
Lower extension of nape strap to prevent dislodging
Excellent rain management system to effectively reduce the flow of water down the neck
Aesthetic, aerodynamic look with smooth finish – solid colour resin for a permanent, no-chip, no-peel finish
Designed for use in industries where there is a hazard, which can damage skull
Available in non-vented fusion (Electrical resistance up to 2 kVA electrical power)

APPLICATION

Protects head from falling objects
Protects splashes, spatters etc.

STORAGE

Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)
Shell may be stored in the dark for up to 5 years
Do not store in direct / high heat or sunlight as this may distort the shell

CLEANING	WEIGHT	PACKING
Clean using warm soapy water and soft cloth	Slip fit - 352 grams, Ratchet fit - 357 grams	50 pieces per carton
Do not use solvents or abrasives		