

# CLEAN AGENT PORTABLE EXTINGUISHER

## FEATURES

- For Class A/B/C and electrical Fire.
- HFC 236fa/FE36 clean agent gas : UL listed and ODP = 0
- BIS Approved and ISI marked.
- Brass chrome plated valve- squeeze operation.
- UV Resistant - High quality Pure Polyester (PP) powder coating.
- Unique Gauge Testing System (UGTS) mechanism.
- Easy to maintain, recharge & service.
- Large loop Stainless steel Pull pin.
- Controllable discharge.



Class A



Class B



Class C



Electrical



CE



ISI

Chemours (Earlier known as DuPont)  
FE 36 Clean Agent Approvals



## PERFORMANCE DATA

MODEL ( RQ SERIES )**	KCARQ-2	KCARQ-4	KCARQ-6
MODEL ( HQ SERIES )	KCAHQ-2-FE36	KCAHQ-4-FE36	KCAHQ-6-FE36
Capacity	2 kg	4 kg	6 kg
Design	Hose & Nozzle	Hose & Nozzle	Hose & Nozzle
Fire Rating	1A : 21B	2A : 34B	2A : 55B
Fire Rating (As per EN)	6A : 21B	8A : 34B	8A : 55B
Height (Approx.)	410 mm	490 mm	530 mm
Diameter (Approx.)	106 ± 5 mm	140 ± 5 mm	150 ± 5 mm
Average Discharge time	9 Sec	14 Sec	22 Sec
Average Range of throw	3 m	3.5 m	4 m
Average % Discharge	96%	96%	96%
Operating Temperature	-30 °C to +60 °C		
Service/Max. service/Test Pressure	10 / 12 / 35 bar		
Expelling Agent	Nitrogen (UHP Grade)		
Empty/Full/Shipping Weight (Aprx.)	2.1 / 4.1 / 4.5 kg	3.1 / 7.1 / 7.5 kg	3.6 / 9.6 / 10.1 kg
Packing Standard	Corrugated Box		
Mounting Bracket	Vehicle / Wall bracket	Wall Bracket	
Approvals	BIS (RQ Series) / BIS & CE (HQ Series)		