

# CLEAN AGENT PORTABLE EXTINGUISHER

## SS FINISH

### FEATURES

- For Class A/B/C and electrical Fire.
- HFC 236fa/FE36 clean agent gas : UL listed and ODP = 0
- BIS Approved and ISI marked.
- Smooth Finish stainless steel body to give aesthetic impression.
- CE marked brass chrome plated valve- squeeze operation.
- UV Resistant - High quality Pure Polyester (PP) powder coating.
- Unique Gauge Testing System (UGTS) mechanism.
- Helium Leak Detection- tested leak rate up to  $1 \times 10^{-8}$  mbar.l/sec
- Easy to maintain, recharge & service.
- Large loop Stainless steel Pull pin.
- Controllable discharge.



Class-A



Class-B



Class-C



Electrical



CE



ISI



### PERFORMANCE DATA

MODEL	KCASSHQ-2-FE36	KCASSHQ-4-FE36	KCASSHQ-6-FE36
Capacity	2 kg	4 kg	6 kg
Design	Hose & Nozzle	Hose & Nozzle	Hose & Nozzle
Fire Rating	1A : 21B	2A : 34B	2A : 55B
Fire Rating (As per EN)	5A : 21B	8A : 34B	8A : 55B
Height (Approx.)	440 mm	500 mm	560 mm
Diameter (Approx.)	110 ± 5 mm	140 ± 5 mm	150 ± 5 mm
Average Discharge time	9 Sec	14 Sec	22 Sec
Average Range of throw	3 m	3.5 m	4 m
Average % Discharge	96%	96%	96%
Operating Temperature		-30 °C to +60 °C	
Service/Max. service/Test Pressure		10 / 12 / 35 bar	
Expelling Agent		Nitrogen (UHP Grade)	
Empty/Full/Shipping Weight (Aprx.)	1.6 / 3.6 / 4.0 kg	2.5 / 6.5 / 6.9 kg	2.8 / 8.8 / 9.3 kg
Packing Standard		Corrugated box	
Mounting Bracket	Vehicle / Wall bracket	Wall Bracket	Wall Bracket
Approvals		BIS & CE	