

FOAM & WATER PORTABLE EXTINGUISHERS

STORED PRESSURE

FEATURES

- Class A/B Fire: AFFF (Aqueous Film Forming Foam).
- Class A Fire: Water.
- BIS Approved and ISI marked.
- Brass chrome plated valve- squeeze operation.
- Air aspirated nozzle to provide high fire rating (Foam extinguisher)
- Hydraulically tested as per standard with anti-corrosive treatment.
- UV Resistant - High quality Pure Polyester (PP) powder coating.
- EPDM Rubber braided hose - High flexibility and less prone to cracks.
- Unique Gauge Testing System (UGTS) mechanism.
- Easy to maintain, recharge & service.
- Large loop Stainless steel Pull pin.
- Controllable discharge.

Water Type Suitable for Class A Fire Risk



Class A

Foam Type Suitable for Class A and Class B Fire Risk



Class A



Class B



PERFORMANCE DATA

TYPE	FOAM		WATER	
	KFMSRQ-6	KFMSRQ-9	KFWSRQ-6	KFWSRQ-9
MODEL (RQ Series)	KFMSRQ-6	KFMSRQ-9	KFWSRQ-6	KFWSRQ-9
MODEL (HQ Series)	KFMSHQ-6-AR	KFMSHQ-9-AR	-	-
Capacity	6 Ltr	9 Ltr	6 Ltr	9 Ltr
Design	Hose & Nozzle	Hose & Nozzle	Hose & Nozzle	Hose & Nozzle
Fire Rating	3A : 89B*	4A : 144B	2A*	3A
Fire Rating (As per EN) (HQ Only)	13A : 89B	27A : 163B	2A*	3A
Height (Approx.)	530 mm	575 mm	530 mm	575 mm
Diameter (Approx.)	160 ± 5 mm	160 ± 5 mm	150 ± 5 mm	160 ± 5 mm
Average Discharge time	22 Sec	35 Sec	22 Sec	35 Sec
Average Range of throw	6 m	6 m	5 m	6 m
Average % Discharge	96%	97%	96%	97%
Operating Temperature	+5 °C to +60 °C			
Service/Max. service/Test Pressure	15 / 18 / 35 bar			
Expelling Agent	Nitrogen (UHP Grade)			
Empty/Full/Shipping Weight (Aprx.)	3.6 / 9.6 / 10 kg	4.9 / 13.9 / 14.4 kg	3.6 / 9.6 / 10 kg	4.9 / 13.9 / 14.4 kg
Packing Standard	Corrugated box			
Mounting Bracket	Wall Bracket			
Approvals	-	BIS	-	BIS
Approvals	CE	BIS & CE	-	-

Note

1. * Indicates factory tested
2. SS Lever & handle available on request

Caution : Don't use on Electrical Fire.