



F33NBG

F33NBG

Material used & Specifications

Base material:

Coating:- NBR compound coated

Liner: blended with UHMWPE, Polyamide, Polyester and Spandex fibre

Binding: -Colour coded overlock binding polypropylene yarn (07-Red, 08-Yellow, 09-Brown, 10-Black)

Sizes

7, 8, 9, 10, 11

Color

Liner Color: Grey

Coating Color: Black

Features:

13 Gauge seamless knitting construction
Open back configuration for better ventilation,
Ergonomically correct design conforms snugly to the natural shape of the hand, increasing comfort and reducing hand fatigue,
Colour coded overlock binding helps to identify different sizes,
Nitrile dipped palm provides excellent puncture and abrasion resistance properties, also provide assistance to handling chemicals and oils.

Specifications

Gauge: 13

Weight: 620-870 g/dzp

Finishing: Sandy Finish



NITRILE GLOVES

Cut Resistant Level 3 Seamless Nitrile Coated Gloves Blended with UHMWPE Fiber, Sandy Finish.



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City

Kolkata 700091, India

T: +E : safety@mallcom.in, w : www.mallcom.in



Safe hands!!

Limits to use

Do not use this glove out of its usage specifications defined in the instructions above. This glove does not contain substance known as being carcinogenic, neither toxic, nor likely to cause allergies to the sensitive people.

Instructions for storage:

Store in a cool, dry place; away from frost and light in their original packaging.

Our engineered high cut resistant UHWMPE blended TUF® yarn with nitrile coated surface provide, dexterity and mechanical resistant

Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines

Instructions for cleaning:

No specific cleaning or maintenance for this type of glove.

Packaging Instruction:

1 dozen pairs in a polybag
 10 poly bags in a carton
 120 pairs in a carton
 (300 pairs/carton option also available)



Performance according to EN 388:2003 :
 4. Resistance to abrasion (from 0 to 4)
 3. Resistance to cut (from 0 to 5)
 4. Resistance to tear (from 0 to 4)
 3. Resistance to puncture (from 0 to 4)



Applications:

Construction Works.
 Lumber and mill works
 Glass sheet handling.
 Metal/aluminium sheet handling
 Installing fence / barb wire
 Machine parts assembling disassembling



MALLCOM INDIA LTD
 EN 12, Sector V, Salt Lake City
 Kolkata 700091, India
 T: +E: safety@mallcom.in, w: www.mallcom.in