



Scan Here For More Info



UD 91 – Safety Spectacle

STANDARD : ANSI Z87.1, EN 166, CE

INDUSTRY	IDEAL APPLICATIONS
Construction & projects	Material handling
Cement	Dusty area
Automotive	Assembly line
Power & utilities	Packaging
Metals & minings	Medical applications

SPECIAL FEATURES



COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	10 base curve, wrap around design w/side protection
Nose piece	Polycarbonate	Universal, integral to lens
Temple	Polycarbonate	Spatula with soft tip end
Tip	TPE	Red Colour Slip on the temple
Hinge	Polycarbonate	2 barrel type
Screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-12	F (45m/s)	K	21 g.

FEATURES
Polycarbonate temple with polycarbonate lens
Wraparound lens provides perfect impact protection around the eyes
Hard coating on lens
Lens filters out 99.9% of harmful UV light
One-piece lens, with dual 10 base curvature
Modern temple design & soft temple tips contours to fit head shapes without stress
Credibly light, resilient & durable protective eyewear for all day wear
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APPLICATION
Protects eyes exposed to low-level impacts
Best used for protection against flying small fragments

STORAGE
Can be stored in the dark for up to 2years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING	PACKING
Clean it with the soft cloth	100 pieces per cartoon

