



B33NBG

#### Features:

The optimal combination of cut resistance, comfort and dexterity,  
Open back configuration for better ventilation,  
Ergonomically correct design conforms snugly to the natural shape of the hand, increasing comfort and reducing hand fatigue,  
Colour coded over lock binding helps to indentify different sizes,  
Nitrile dipped palm provides excellent puncture and abrasion resistance properties, also provide assistance to handling chemicals and oils.

## B33NBG

#### Material used

Base material- Liner blended DYNEEMA®,  
Steel filament , Spandex fibre  
Palm and finger tips- NBR compound coated  
Binding –Colour coded over lock binding  
polypropylene yarn (07-Red, 08-Yellow, 09-Brown, 10-Black)

#### Sizes

7, 8, 9, and 10

#### Colour:

Palm – Black  
Back - Grey

#### Specifications

Gauge: 13

Weight: 60g/pair

Finishing: Sandy Finish



## DYNEEMA® GLOVES

Cut Resistant Level 5 Seamless  
Nitrile Coated Gloves Blended  
with Steel based Fiber, Sandy  
Finish.



#### MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City  
Kolkata 700091, India

T: +E : [safety@mallcom.in](mailto:safety@mallcom.in), w : [www.mallcom.in](http://www.mallcom.in)



## Safe hands!!

### Limits to use

Do not use this glove out of its usage specifications defined in the instructions above. This glove does not contain substance known as being carcinogenic, neither toxic, nor likely to cause allergies to the sensitive people.

### Instructions for storage:

Store in a cool, dry place; away from frost and light in their original packaging.

Our engineered high cut resistant blended Dyneema® yarn with nitrile coated surface provide, dexterity and mechanical resistant

### Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines

Instructions for cleaning:

No specific cleaning or maintenance for this type of glove.

### Packaging Instruction:

1 dozen pairs in a polybag  
10 poly bags in a carton  
120 pairs in a carton

EN 388




4441D

4 : Resistance to abrasion (from 0 to 4)  
4 : Resistance to cut (from 0 to 5)  
4 : Resistance to tear (from 0 to 4)  
1 : Resistance to puncture (from 0 to 4)  
D : TDM blade cut resistant level (from A to F)



### Applications:

Automotive Aftermarket:  
Chassis assembly, body trimming  
Foundry operations  
Machinery and Equipment:  
Handling materials with sharp or rough edges  
Handling metal sheets & panels  
Handling parts in high heat areas  
Handling parts with sharp, rough edges



### MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City  
Kolkata 700091, India

T: +E: [safety@mallcom.in](mailto:safety@mallcom.in), w: [www.mallcom.in](http://www.mallcom.in)