



PR 14
Polyamide Rope

| INDUSTRY | IDEAL APPLICATIONS | SPECIAL FEATURES | | |
|---|--------------------|--|--|---|
| Construcion | Working at Height |  FALL ARREST |  STRONG |  TEMPORARY ANCHORAGE |
| Telecommunicaion | | | | |
| Transmission | Fall Arrest | | | |
| MECHANICAL CHARACTERISTICS | | | | |
| Rope Material - Polyamide Rope | | Breaking Strength - 38 kN | | |
| Rope Dia - Ø 14 mm Rope | | Minimum Breaking Strength - 15 kN (for 10.5mm), 22kN (for 14mm) | | |
| PHYSICAL PARAMETERS | | TEST COMPLIANCE - STATIC STRENGTH | | |
| Sitching Threads - High tenacity virgin multi-filament polyester | | Withstands a load of 23 kN for 3 minutes each attachment element | | |
| One side snap hook PN 121 and other side end stop knot | | TEST COMPLIANCE - DYNAMIC STRENGTH | | |
| Metal Components - High Quality Alloy Steel, Zinc Plated, free from any Sharp Edges | | When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is less than 1.5 meter | | |
| FEATURES | | AVAILABLE LENGTH | | |
| Tie of Anchor line made of Polyamide Twisted Rope | | Rope Dia - Ø 14 mm - 10, 20, 30, 40, 50, 60,70, 100, 150, 200 meter | | |
| Loops at other end | | STORAGE | | |
| Strength: 38 kN | | Store Webbing sling in a dry area away from ultra violet rays | | |
| Standard: Conforms to Conforming to EN 354:2010, EN 355:2002 | | Do not store in direct / high heat or sunlight as this may distort the colour | | |
| MARKINGS | | Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold | | |
| Manufacturers Logo, details & mailing address | | CLEANING | | PACKING |
| Model No., Batch No., Serial No. | | Use clean piece of cloth to wipe the dust | | 1 piece per Bag |
| Year of Manufacturing | | | | |
| Material | | | | |
| Approvals & EN | | | | |
| Instrucion Pictogram | | | | |

