



PR 14
Polyamide Rope

INDUSTRY	IDEAL APPLICATIONS	SPECIAL FEATURES		
Construcion	Working at Height	 FALL ARREST	 STRONG	 TEMPORARY ANCHORAGE
Telecommunicaion				
Transmission	Fall Arrest			
MECHANICAL CHARACTERISTICS				
Rope Material - Polyamide Rope		Breaking Strength - 38 kN		
Rope Dia - Ø 14 mm Rope		Minimum Breaking Strength - 15 kN (for 10.5mm), 22kN (for 14mm)		
PHYSICAL PARAMETERS		TEST COMPLIANCE - STATIC STRENGTH		
Sitching Threads - High tenacity virgin multi-filament polyester		Withstands a load of 23 kN for 3 minutes each attachment element		
One side snap hook PN 121 and other side end stop knot		TEST COMPLIANCE - DYNAMIC STRENGTH		
Metal Components - High Quality Alloy Steel, Zinc Plated, free from any Sharp Edges		When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is less than 1.5 meter		
FEATURES		AVAILABLE LENGTH		
Tie of Anchor line made of Polyamide Twisted Rope		Rope Dia - Ø 14 mm - 10, 20, 30, 40, 50, 60,70, 100, 150, 200 meter		
Loops at other end		STORAGE		
Strength: 38 kN		Store Webbing sling in a dry area away from ultra violet rays		
Standard: Conforms to Conforming to EN 354:2010, EN 355:2002		Do not store in direct / high heat or sunlight as this may distort the colour		
MARKINGS		Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold		
Manufacturers Logo, details & mailing address		CLEANING		PACKING
Model No., Batch No., Serial No.		Use clean piece of cloth to wipe the dust		1 piece per Bag
Year of Manufacturing				
Material				
Approvals & EN				
Instrucion Pictogram				

