




PROTON
Retractable Fall Arrester

STANDARD : CONFORMING TO EN360:2002

INDUSTRY	IDEAL APPLICATIONS	SPECIAL FEATURES
Construction	Working at Height	 FALL ARREST
	Ladder Climbing	
	Fall Arrest	

MECHANICAL CHARACTERISTICS
Breaking Strength - 15 kN
Breaking Force - Less than 6 kN
Fall Arrest Distance - 1.5 m (Maximum)
Temp. Range - -30°C to 50°C

PHYSICAL PARAMETERS
Robust & durable casing made from high impact glass field nylon
Has a swivel anchorage eye at one end
Snap hook equipped with fall indicator and swivel action

RETRACTABLE LANYARD
Material - Stainless Steel
Diameter - Φ4.8 mm
Breaking Strength - Greater than 15 kN

TEST COMPLIANCE - STATIC STRENGTH
When subjected to a fall with a rigid mass of 100 kg., the breaking force is less than 6 kN, and the arrest distance is less than 1.5 m.



FEATURES
Wire rope type retractable fall arrester
High Impact resistance polyamide casing
Stainless steel rope with swivel snap hook
In case a fall occurs, the automatic braking system in the block immediately arrests the fall
Included conduit rope
Maximum load capacity : 100 kg

AVAILABLE LENGTH
5, 6, 7, 10, 12, 15 & 18 mtr

STORAGE
Store the retractable in a dry area away from ultraviolet rays
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Instrucion Pictogram

CLEANING
Use clean piece of cloth to wipe the dust

PACKING
4 pieces per carton

Udyogi