
















ULTRATEK
Safety Harness

STANDARD : CONFORMING TO EN 361:2002,
EN 1497:2007, EN 813:2008, EN 358:2018, IS 3521:Part 1:2021  

INDUSTRY	IDEAL APPLICATIONS
Contrucion	Rescue
Telecom	Rope Access
Transmission	Ladder Climbing
-	Work Posiioning
-	Fall Arrest

SPECIAL FEATURES					
 FALL ARREST	 RESTRAINT	 CLIMBING	 POSITIONING	 LOWERING	
 FRONT CLIMB	 LOWERING IN SUSP. POS	 CLASS-L	 CLASS-A	 CLASS-P	 CLASS-D

WEBBING MATERIAL	WEBBING WIDTH
AZO free dyed syntheic Polyester	44 +/- 1 mm

WEBBING BREAKING STRENGTH
22kN (Min)

STITCH THREADS MATERIAL	STITCH THREADS COLOUR
High-tenacity virgin multifilament polyester	White

METAL COMPONENTS	HARNESS COLOUR	WEIGHT
High quality alloy steel, zinc plated, free from any sharp edges	Black	2200 grams

TEST COMPLIANCE - STATIC STRENGTH
Tested at each attachment element with a force of 15 KN applied for 3 min.



TEST COMPLIANCE - DYNAMIC STRENGTH
When tested at ea W rest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 mt.

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72