Bright Star Lighting Products

Unit Dimensions

Engineering Data Sheet: 2206

Unit Information

Model #: 2206 / Item #07050 UPC-IC (12 Digit): 01673070502

Length: 8.2 in. (20.9 cm) Width: 4.9 in. (12.4 cm) Height: 5.6 in. (14.2 cm)

Master Pack Dimensions

Weight: 5.8 lbs. (2.6 kg) Cube: $0.93 \text{ ft}^3 (0.02 \text{ m}^3)$

Quantity: 6

Safety Approvals

UL/CUL: Class I, Div 1, Group C & D

Class II, Div 1, Group G Operating Temp T3B

Class I Zone 1 Group IIB & IIA

MSHA Approved



Specifications

Power Source: Alkaline or Carbon Zinc 6V

Lantern Battery Bulb/Lamp: KPR 113 Bulb/Lamp Life: 15 Hours

Light Output: 50,000 Beam Candlepower Weight (Without batteries): 14.0 oz

Components

Lens Ring: Polypropylene (Black) Lens: Unbreakable Tuflexx® Reflector: Polycarbonate

Lantern Box: Polypropylene (Safety Orange) Battery Connector: ABS, Spring brass & tin

coated steel

Switch: Rubber & co-polymer

Product Features

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Waterproof & floating
- Krypton Bulb
- Alkaline Battery
- Switch guard protects switch on impacts
- Optional stand
- Spare bulb compartments
- Oversized reflector for more light output
- Glove size handle
- Circuit Breaking Mechanism

Accessories Description

20414 KPR113 Bulb

