



Scan Here For More Info



UD 39 – Safety Goggles

STANDARD : ANSI Z87.1, EN 166, CE

INDUSTRY

Oil & gas
Pharmaceutical
Iron & steel
Automotive
Power & utilities

IDEAL APPLICATIONS

Grinding
Chemical handling
Labs
Paint shop
Medical application

SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



CHEMICAL SPLASH PROTECTION



MEDIUM IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	Single lens
Body	PVC	Flexible fitting goggle with indirect vents
Nose piece	PVC	Integral to universal, integral to frame temple
Head band	Nature rubber inside and polyester outside	Adjustable elastic

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	B	K	70 g.

FEATURES

Polycarbonate lens with soft PVC frame & body

Lens provides medium velocity impact & splash protection around the eyes

Hard coating on lens

Lens filters out 99.9% of harmful UV light

Fully adjustable headband attached to fits most users

Soft goggle body conforms to facial contours for a very comfortable fit to ensure for long time wearing

Universal fit soft nose bridge conforms to facial contours to ensure a comfortable fit

Venting system that circulates air, yet prevent dust

Incredibly light, resilient, durable & over the glass protective eyewear for all day wear

Suitable for different work environment & for both men and women

APPLICATION

Protects eyes exposed to medium level impacts

Best used for protection againsts flying small fragments, liquid splashes, fumes, sparks etc.

Also protects against irritating mist and potentially infectious materials (lab environment)

STORAGE

Can be stored in the dark for up to 2years

Do not store in direct / high heat or sunlight as this may distort the colour

Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING

Clean it with the soft cloth

PACKING

50 pieces per carton

Udyogi Plastics Private Limited

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72